

THERMAL INKJET PRINTER

©2022 Cyklop International - All rights reserved - Specifications are subject to change without notice.

The CM 750 has been designed to meet the very exacting standards and flexibility demanded from an industrial printer in today's fast moving production environments.

Reliability of operation in the harshest environments. Quality of printing monitored and maintained to deliver perfect code every print. Simplicity of setup, service and operation through a highly visible 10" Touch screen. Cost Saving features of single part service and solvent consumption saving system. Powerful and flexible print data options through network or local scanners. The CM750 has it all covered.

Advantages

- 10" color touch screen featuring a simple to operate interface
- Up to 5 lines of high quality print from multiple data sources
- Modular ink system
- IP55 industrial structure
- Quick, clean, fluids addition
- Maintenance friendly modular print head
- A simple high resolution user interface
- Single filter module





Technical data	
Screen size / type	Color 10 inch TFT LCD Touchscreen
Power supply	AC 100 V - 240 V, 50 / 60 Hz, 1.4 A. Maximum power Consumption: 138 W
Environment	5 – 45 °C, Humidity 90 %
Conformity	CE certification
Warranty	12 months
Industrial Protection	IP 55
Print data source	USB, RS232, TCP/IP
Nozzle	60u / 70u
Print lines	4 lines x7 high, 5 lines x5 high
Print fonts	5x5, 7x55, 9x7, 11x9, 16x11, 19x14, 24x16, 32x24
Cartridge volume	750 ml
Total ink volume	1,250 ml

Cyklop UK Limited Unit 2, Generation Business Park Barford Road St. Neots Cambridgeshire PE19 6YQ

+44 1480 216777 www.cyklop.co.uk info@cyklop.co.uk



